



## Compressed Sheet with Aramid Fiber / SBR Binder

## Application:

NA1035 is a very good general service SBR binder based gasket material that has numerous applications in the process industries handling media like; mild acids and alkalis, water, brine, saturated steam, air, industrial gases, general chemicals, neutral solutions.

## **Construction:**

NA1035 is a compressed fiber sheet gasket material produced from a combination of Aramid Fibers, Inorganic Fillers and bonded with Styrene-Butadiene Rubber (SBR). It is manufactured under rigorous quality control standards that are registered under ISO-9001 certification.

Availability	Size: 59 x 63 in or 59 x 126 in
	Thickness: 1/64", 1/32", 1/16", 1/8"
Temperature	Continuous Service: 518° F (270° C)
	Maximum Service: 716°F (380°C)
Pressure	Continuous Service: 725 psi (50 bar)
	Maximum Service: 1015 psi (70 bar)
Color	Off White - NA1035W
	Grey/Black - NA1035B
ASTM Line Call Out F104	F712940E44M9



## **Typical Physical Properties:**

112 (1.80)		
7 – 17		
50		
27		
Thickness Increase - ASTM F146 - % maximum		
40		
20		
Weight Increase - ASTM F146 - % maximum		
30		
30		
32		

Note: ASTM values for 0.8 mm and DIN values for 2.0 mm thick sheets.

Properties and application parameters shown throughout this data sheet are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult TEADIT. Failure to select proper sealing products could result in property damage and/or serious personal injury. Specifications are subject to change without notice; this edition cancels all previous issues.